

IN THE CLAIMS

1 1. (currently amended) A device for cleaning an inner pipe which comprises:

2 a nozzle head comprised of a feed borehole axially disposed therein, at least two rotation  
3 nozzles communicating with the feed borehole and extending perpendicularly from the  
4 longitudinal axis of the feed borehole, at least two cleaning nozzles communicating with the feed  
5 borehole and extending downwardly at an angle from the longitudinal axis of the feed borehole,;  
6 and a shaft;

7 a rinsing nozzle communicating with the feed borehole and extending upwardly at an  
8 angle from the longitudinal axis of the feed borehole; and

9 an outer sleeve adapted to receive a hollow rod, the shaft being received in the outer  
10 sleeve whereby when the device is inserted into an inner pipe and a medium is flowed through  
11 the borehole and out of the rotation nozzles a force is generated when the medium emerging  
12 from the rotation nozzles contacts the wall of the inner pipe which force causes the nozzle head  
13 to rotate, the outer sleeve comprising a first means for preventing the nozzle head from  
14 descending into the inner pipe disjoined from the outer sleeve when the nozzle head has a first  
15 break, the cross-section of which lies above the first means for preventing and a second means  
16 for preventing the nozzle head from descending into the inner pipe disjoined from the outer  
17 sleeve when the nozzle head has a second break, the cross-section of which lies above the second  
18 means for preventing, the first means for preventing comprising an intermediate sleeve  
19 interposed between the outer sleeve and the shaft, the intermediate sleeve having a shoulder that  
20 prevents the nozzle head from descending into the pipe disjoined from the outer sleeve when the  
21 nozzle head has the first break.

2. (original) The device of claim 1 which further comprises a first and second radial bearing and a first and second axial bearing, the bearings being disposed between the shaft and the outer sleeve.

3. (original) The device of claim 2 wherein the radial bearings are cylindrical.

4. (currently amended) The device of claim 3 wherein the ~~first means for preventing~~  
~~comprises an intermediate sleeve interposed between the outer sleeve and the shaft and is~~  
positioned above the first radial and axial bearings, ~~the intermediate sleeve having a shoulder~~  
~~that prevents the nozzle head from descending into the pipe disjoined from the outer sleeve when~~  
the nozzle head has the first break.

5. (original) The device of claim 4 wherein the shaft further comprises an annular groove and the second means for preventing comprises a protuberance that is secured to the outer sleeve and projects into the annular groove, the protuberance being positioned below the second radial and axial bearings, the protuberance the nozzle head from descending into the pipe disjoined from the outer sleeve when the nozzle head has the second break.

6. The device of claim 1 wherein the nozzle head further comprises:  
at least one water outlet in communication with the feed borehole and positioned upwardly from the longitudinal axis of the feed borehole; and  
a gap formed in between the water outlet and the outer sleeve, the gap being filled with medium when the medium is flowed through the feed borehole and emerges out of the water outlet.

7. (currently amended) ~~The device of claim 1~~ A device for cleaning an inner pipe which  
comprises:

3        a nozzle head comprised of a feed borehole axially disposed therein, at least two rotation  
4        nozzles communicating with the feed borehole and extending perpendicularly from the  
5        longitudinal axis of the feed borehole, at least two cleaning nozzles communicating with the feed  
6        borehole and extending downwardly at an angle from the longitudinal axis of the feed borehole,;  
7        and a shaft;

8        a rinsing nozzle communicating with the feed borehole and extending upwardly at an  
9        angle from the longitudinal axis of the feed borehole; and  
10       an outer sleeve adapted to receive a hollow rod, the shaft being received in the outer sleeve  
11       whereby when the device is inserted into an inner pipe and a medium is flowed through the  
12       borehole and out of the rotation nozzles a force is generated when the medium emerging from  
13       the rotation nozzles contacts the wall of the inner pipe which force causes the nozzle head to  
14       rotate, the outer sleeve comprising a first means for preventing the nozzle head from descending  
15       into the inner pipe disjoined from the outer sleeve when the nozzle head has a first break, the  
16       cross-section of which lies above the first means for preventing and a second means for  
17       preventing the nozzle head from descending into the inner pipe disjoined from the outer sleeve  
18       when the nozzle head has a second break, the cross-section of which lies above the second means  
19       for preventing; which further comprises and a vortex brake disposed between the shaft and the  
20       outer sleeve.

1       8.       (original)       The device of claim 7 wherein the vortex brake comprises:  
2              an inner ring enveloping and joined to at least a portion of the shaft;  
3              a first outer ring enveloping at least a portion of the inner ring; and

4 a magnet enveloping at least a portion of the inner ring, the magnet and the first outer  
5 ring forming a stator, the rotation of the inner ring within the stator being controlled by the  
6 magnetic force being applied to the inner ring from the magnet.

1 9. (original) The device of claim 8 wherein the vortex brake further comprises a gap  
2 formed between the stator and the inner ring, the gap being adapted to receive the medium.

1 10. (original) The device of claim 9 wherein the magnet comprises at least two magnets  
2 encapsulated in a second outer ring.

1 11. (original) The device of claim 10 wherein the stator comprises a plurality of outer  
2 rings that envelop at least a portion of the inner ring, the number of outer rings determining the  
3 region that the inner ring is enveloped by the second outer ring.

1 12. (original) The device of claim 1 wherein the shaft comprises a first part and a second  
2 part, the first part being received in the second part and being constructed and arranged to allow  
3 axial movement of the second part within the first part and to prevent rotational movement of the  
4 second part within the first part.

1 13. (original) The device of claim 12 wherein the shaft further comprises a damping  
2 chamber in communication with a chamber, the damping chamber communicating with the  
3 chamber through a damping gap.

1 14. (original) The device of claim 2 wherein the bearings are comprised of stainless  
2 steel, the bearings being adapted to be cooled by the medium when the medium is provided  
3 between the nozzle head and the outer sleeve.

1 15. (original) The device of claim 1 wherein the nozzle head further comprises:  
2 an aperture;  
3 a recess having a top end;

4 a plunger comprised of a base and a tip and disposed within the recess; and

5 means for biasing the plunger in a first position wherein the tip extends through the  
6 aperture and outwardly from the nozzle head.

1 16. (original) The device of claim 15 wherein the nozzle head further comprises a spring  
2 having a first end and a second end, the first end contacting the base and the second end  
3 contacting the top end whereby when a force is applied to the tip and the plunger is in the first  
4 position, the spring compresses allowing the plunger to move upwardly within the recess to a  
5 second position.

1 17. (original) The device of claim 16 wherein the plunger is concentrically disposed  
2 within the nozzle head.

1 18. (original) The device of claim 16 wherein the nozzle head further comprises at least  
2 two jet nozzles positioned within the nozzle head, the jet nozzles being in communication with  
3 the feed borehole when the plunger is in the second position thereby allowing the emergence of  
4 medium out of the jet nozzles when the medium is flowed through the borehole and being out of  
5 communication with the feed borehole when the plunger is in the first position thereby  
6 preventing the emergence of medium out of the jet nozzles when the medium is flowed through  
7 the borehole.

1 19. (original) The device of claim 18 wherein the plunger further comprises a plurality  
2 of channel boreholes so constructed and arranged to allow the flow of medium through the  
3 channel boreholes to the rotation nozzles or optionally the cleaning nozzles or optionally the  
4 rotation nozzles and the cleaning nozzles when the medium is flowed through the feed borehole  
5 and the plunger is in the first position.

20. (original) The device of claim 19 wherein the channel boreholes are constructed and arranged to prevent the flow of medium through the channel boreholes to the rotation nozzles or optionally the cleaning nozzles or optionally the rotation nozzles and the cleaning nozzles when the medium is flowed through the feed borehole and the plunger is in the second position.

21. (currently amended) The device of claim 1 wherein the nozzle head further comprises: A device for cleaning an inner pipe which comprises:

a nozzle head comprised of a feed borehole axially disposed therein, at least two rotation nozzles communicating with the feed borehole and extending perpendicularly from the longitudinal axis of the feed borehole, at least two cleaning nozzles communicating with the feed borehole and extending downwardly at an angle from the longitudinal axis of the feed borehole,; and a shaft;

a rinsing nozzle communicating with the feed borehole and extending upwardly at an angle from the longitudinal axis of the feed borehole; and

an outer sleeve adapted to receive a hollow rod, the shaft being received in the outer sleeve whereby when the device is inserted into an inner pipe and a medium is flowed through the borehole and out of the rotation nozzles a force is generated when the medium emerging from the rotation nozzles contacts the wall of the inner pipe which force causes the nozzle head to rotate, the outer sleeve comprising a first means for preventing the nozzle head from descending into the inner pipe disjoined from the outer sleeve when the nozzle head has a first break, the cross-section of which lies above the first means for preventing and a second means for preventing the nozzle head from descending into the inner pipe disjoined from the outer sleeve when the nozzle head has a second break, the cross-section of which lies above the second means for preventing;

20 a front end;

21 and a central nozzle having an aperture, the central nozzle being in communication with  
22 the feed borehole and positioned in the front end whereby when medium is flowed through the  
23 feed borehole and emerges out the aperture, the size of the aperture can be adjusted to regulate  
24 the flow of the medium therethrough.